



# TBP SOLAR

TOP BRAND PRODUCT



**5  
YEARS**

★ WARRANTY ★



**TOP  
QUALITY**

## Free Solar Fuel for life Time

Enjoy hot water anytime



- Available in 100, 150, 200, 250, 300, 500, 1000 LPD capacity & above
- Frosted glass on collector improves efficiency
- Ideal for hard water areas (up to 1500 ppm)
- Inner Tank single CR Steel Sheet Ceramic Filled Epoxy Coating



5 Years  
Warranty\*



Suitable for  
Hard Water\*



Non-Corrosive  
Inner Tank



High efficiency  
Collector




PUF  
Insulation



CR Steel  
Sheet Tank






## ZING ETC WATER HEATER


Capacity LPD	100 LPD	150 LPD	200 LPD	250 LPD	300 LPD	500 LPD Manifold	1000 LPD Manifold
Suitable Ideal Family Size	1 to 3 person	4 to 5 person	6 to 8 person	8 to 10 person	10 to 12 person	18 to 20 person	35 to 40 person
Exptd . Annual Savings Rs:	₹ 11,433	₹ 17,149	₹ 22,866	₹ 28,582	₹ 34,299	₹ 57,167	₹ 1,14,334
No. of Tubes	10 Nos	15 Nos	20 Nos	25 Nos	30 Nos	50 Nos	100 Nos

ETC Tubes Specs	58 mm X 1800 mm, Triple Layer 3 Target Coating , Borosilicate Glass 3.3 , Absorption >0.9
Circulation	Thermosphon Type
Hot Water Out Put Temperature	60° C
Overnight Temperature Drop	0.5° C/hr
Inner Tank protective Coating	CR Steel Sheet Ceramic Filled Epoxy Coating
Inner Tank (MOC/ Thickness)	100 Lpd to 200 Lpd - 1.6mm / 250 Lpd to 500 Lpd - 2 mm / 1000 LPD 2.5 mm
Inner Tank Anode Protection	Magnesium / Aluminium Alloy
Operating Pressure	0.5 Bar for Non pressurized system
Tank Insulation, Thickness & Density	CFC - Free PUF, 50mm Thick, 28-34 Kg/m3 Density
Tank Outer Cladding	Material GI Pre-coated & 0.4mm thick with yellow colour
Electrical back-up provision	Provision in all Tanks
System packing	Card board carton / Wooden Crate Packing, Depending on Tank Size
Accessories	Ss Accessories for assembly
System support structure	MS angle Stand with Powder coated




## ZING FPC WATER HEATER

	NON PRESSURISED								PRESSURISED		
Capacity LPD	100	150	200	250	300	500	1000		100	200	300
Nos of Collector	01	01	02	02	03	04	08		01	02	03
Circulation	Thermosphon Type				Thermosphon Type				Thermosphon Type		
Hot Water Out Put	60° - 65° C*				60° - 65° C*				60° - 65° C*		
Overnight Temperature Drop	0.5° C/hr				0.5° C/hr				0.5° C/hr		
Inner Tank protective Coating	CR Steel Sheet Ceramic Filled Epoxy Coating				CR Steel Sheet Ceramic Filled Epoxy Coating				CR Steel Sheet Ceramic Filled Epoxy Coating		
Inner Tank (MOC/ Thickness)	100 Lpd to 200 Lpd - 1.6mm / 250 Lpd to 1000 Lpd - 2.5 mm /				100 Lpd to 300 Lpd - 2.5mm						
Inner Tank Anode Protection	Magnesium / Aluminium Alloy				Magnesium / Aluminium Alloy						
Operating Pressure	0.5 Bar				3.5 Bar						
Testing Pressure	1.0 Bar				5.0 Bar						
Tank Insulation, Thickness & Density	CFC - Free PUF, 40mm Thick, 28 -34 Kg/m3 Density				CFC - Free PUF, 40mm Thick, 28 -34 Kg/m3 Density						
Tank Outer Cladding	Material GI Pre-coated & 0.4mm thick with yellow colour				Material GI Pre-coated & 0.4mm thick with yellow colour						
Electrical back-up provision	Provision in all Tanks				Provision in all Tanks						
System packing	Card board carton / Wooden Crate Packing, Depending on Tank Size				Card board carton / Wooden Crate Packing, Depending on Tank Size						
Accessories	Non pressurised Fittings				Pressurised Fittings						
System support structure	MS angle Stand with Powder coated				MS angle Stand with Powder coated						



## ULTIMA FPC WATER HEATER

	ULTIMA PRESSURISED						
Capacity LPD	150	200	250	300	500	1000	
No. of Collectors	01	02	02	03	04	08	
Circulation	Thermosphon Type						
Hot Water Out Put	70° C*						
Overnight Temperature Drop	0.5° C/hr						
Inner Tank protective Coating	C.R. Steel Sheet, Ceramic Filled Epoxy Coating						
Inner Tank (MOC/ Thickness)	150 Lpd to 300 Lpd - 4mm / 500 Lpd to 1000 Lpd - 5 mm						
Inner Tank Anode Protection	Magnesium / Aluminium Alloy						
Operating Pressure	5.0 Bar						
Testing Pressure	10.0 Bar						
Tank Insulation, Thickness & Density	CFC - Free PUF, 40mm Thick, 28 -34 Kg/m3 Density						
Tank Outer Cladding	Material GI Pre-coated & 0.4mm thick with yellow colour						
Electrical back-up provision	Provision in all Tanks						
System packing	Card board carton / Wooden Crate Packing, Depending on Tank Size						
Accessories	Pressurised Fittings						
System support structure	MS angle Stand with Powder coated						



Marketing by :



**KRISHI TECHNOLOGIES  
INDIA PRIVATE LIMITED**

# 335, 1st Main Road, 5th Cross, Bhanu Nursing Home Road  
Bommanahalli, Bangalore - 560 068  
Ph: 080 - 25732171, Mobile : 9448484194 / 9844077662  
E-mail : [info@krishitechnologies.com](mailto:info@krishitechnologies.com)  
Website : [www.krishitechnologies.com](http://www.krishitechnologies.com)

Dealer :